

Product profile

PF8

Desktop Printers



- IT-friendly design simplifies deployment and support, especially in networked environments
- Industry-standard connectivity options include fast, internal Ethernet
- Includes popular PrintSet configuration tool for fast set-up and upgrades
- Provides easy migration path for Intermec PC4 and other EPL desktop printers
- Compact footprint for space constrained applications
- Clamshell design makes media loading easy and intuitive
- Double-wall case provides durability
- One-inch ribbon core option (PF8t) maximizes time between roll changes
- Ideal for healthcare, transportation/ courier, retail and office environments

Designed to set a new standard in IT friendliness, the Intermec PF8 provides a compact, easy-to-use bar code printing solution that dramatically simplifies deployment and support. Its quiet, reliable operation and intuitive design make the PF8 the right fit for light duty labeling applications in transportation/ courier, healthcare, in-store retail and office environments.

Easy to Deploy

Available in thermal transfer (PF8t) and direct thermal (PF8d) print technology models, the PF8 is packed with features that simplify deployment and reduce the need for IT support. In particular, the PF8 now includes Intermec PrintSet, a robust configuration tool that has long proven its value across the Intermec industrial printer line. PrintSet provides an easy tool for configuring printer and network settings, downloading fonts and graphics, and upgrading firmware, saving time for both set-up and ongoing maintenance.

The PF8 printers include flexible, industry standard connectivity - including parallel, serial, USB and optional internal Ethernet - enabling easy, drop-in installation in networked environments. With their compact size, common media specifications, and ESIM printer language, the PF8 printers provide an easy migration path from legacy Intermec printers such as the PC4, as well as from other desktop printers using the EPL printer language.

The PF8's off-the-shelf compatibility and certifications with a wide range of business

and healthcare software applications enables users to be up and running quickly, requiring minimal IT support.

Easy to Use

Ideal for customers who are new to label printing or who are making the switch from laser or inkjet printers, the easy-to-use PF8 reduces training needs and trouble tickets. Its double-wall clamshell construction is durable and makes media loading (and reloading) intuitive and virtually trouble-free. Users can depend on the PF8 to consistently deliver reliable, high quality bar code output.

The PF8t thermal transfer printer provides two options: a one-inch or a half-inch ribbon core. The one-inch core accommodates a larger ribbon roll (up to 900 feet), which reduces the need for frequent replacements, minimizes downtime and enables ribbons to be shared with industrial printers. The half-inch core also holds a very large ribbon roll (300 feet).

The Right Fit

With their small footprint and near-silent operation, the PF8 printers are perfect for space-constrained environments and settings such as patient areas and offices. The PF8 printers are the right fit for a wide range of applications, including patient wristband and prescription labeling, shelf and shipping labels, asset labeling, and almost any busy place where users need reliable, easy-to-use bar code printers.

Intermec[®]

Physical Description

The PF8d and PF8t are very compact Direct Thermal or Thermal Transfer printers for self-adhesive labels, non-adhesive tags, or continuous paper strip roll.

Specifications by Model

| | PF8d | PF8t |
|----------------------------|-------------------|--|
| Length: | 218 mm (8.58 in) | 285 mm (11.2 in) |
| Height: | 116 mm (4.56 in) | 172 mm (6.77 in) |
| Width: | 168 mm (6.61 in) | 226 mm (8.9 in) |
| Weight: | 2.0 kg (4.41 lbs) | 2.5 kg (5.07 lbs) |
| Print Resolution: | 203 dpi | 203 dpi standard; 300 dpi optional |
| Real-time Clock: | Yes | Not standard; field installable option |
| Compact Flash Slot: | No | Yes |

Print Specifications

Maximum Label Width: 118 mm (4.65 in)

Maximum Label Length:

Standard: 203 dpi - 1727 mm (68 in)
300 dpi - 900 mm (35 in)

Print Direction: Prints text, bar codes and graphics in all four directions

Print Resolution: 8 dots/mm (203 dpi) or 12 dots/mm (300 dpi) (PF8t)

Print Width: 203 dpi - max. 104 mm (4.1 in)
300 dpi - max. 106 mm (4.2 in)

Printing Speed:

Selectable up to 4 ips (101.6 mm) for 203 dpi
2 ips (50.8 mm) for 300dpi

Media Specifications

Label Roll -

Maximum Diameter: 127 mm (5 in)

Core Diameter: Min. 25.4 mm (1 in)

Max. 38.1 mm (1.5 in)

Paper Width: Max. 118 mm (4.65 in)

Min. 25.4 mm (1 in)

Label Length: Min. 12 mm (0.5 in)

Labels: A wide selection of stock and custom size labels are available.

Ribbon Roll - PF8t-0.5"

Max. length: 3.588 in (91.1 m)

Min width: 2.36"

Max width: 4.33"

Core: 0.5" ID (12.7mm ID), with notches

Ribbons: A wide selection of widths and formulations available.

Ribbon Roll - PF8t-1"

Max. length: 10.800 in (274.32 m)

Min width: 2.36"

Max width: 4.33"

Core: 1.0" ID (26 mm ID) with notches

Ribbons: A wide selection of widths and formulations available.

Connect to Print™

The printer comes with all included: software, drivers, USB cable, parallel cable (PF8t), and a handy QuickGuide to facilitate getting started, and a PrinterCompanion CD with label design program, Windows™ driver and documentation.

Software

Printer Command Language: ESIM (EPL2)

Applications/Drivers: Interdriver™ Windows

Printer Driver

Intermec Label design and print package

PrintSet for printer configuration, font and

firmware downloading tool

Characters/Fonts

Five resident alphanumeric fonts; expandable 8 times horizontally and 9 times vertically. Four double-byte fonts including Korean, Japanese, Chinese GB2312 and Chinese BIG-5. Printing of graphics, symbols, and downloading of additional fonts is also possible.

Bar Code Symbolologies

All major 1-dimensional bar code symbolologies are available, plus five 2-dimensional codes: MaxiCode, PDF417, DataMatrix, QR-Code, and Composite Code EAN/ECC for EAN/UCC 128 w/ CC-C.

Environment

+5° to +40°C (+40° to +104°F)

Humidity

10-90% RH non-condensing

Power Supply

Separate power supply unit -

Input: 100-240 V AC/50-60 Hz, 1.9 A

Output: 24 V DC, 3.0 A

Memory

Standard: 4 MB Flash, 8 MB SDRAM

Optional: 1GB Compact Flash (PF8t)

Interface

Standard: RS-232C, USB v.2.0, and Centronics/Parallel

Optional: Internal Ethernet 10/100 Mbps, External Ethernet Adaptor

Protocol

XON/XOFF, RTS/CTS

Operator Control

One multi-color LED indicator lamp and one Print/Feed key

Regulatory Approvals

CE, FCC Class A, cULus, UL, GS,TUVGS, CCC, C-TICK, BSMI

Options

Serial communication cable, RS-232 Scanner Cable, IEEE 1284 Parallel Cable, Self-strip, Cutter unit, 300 dpi, 1 GB Compact Flash with Real-Time Clock (PF8t).

North America

Corporate Headquarters

6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348-2600
Fax: (425) 355-9551

North Latin America

Headquarters Office

Mexico
Phone: +52 55 52-41-48-00
Fax: +52 55 52-11-81-21

South Latin America

Headquarters Office

Brazil
Phone: +55 11 5502.6770
Fax: +55 11 5502.6780

Europe/Middle East & Africa Headquarters Office

Reading, United Kingdom
Phone: +44 118 923 0800
Fax: +44 118 923 0801

Asia Pacific

Headquarters Office

Singapore
Phone: +65 6303 2100
Fax: +65 6303 2199

Internet

www.intermec.com
Worldwide Locations:
www.intermec.com/locations

Sales

Toll Free NA: (800) 934-3163
Toll in NA: (425) 348-2726
Freephone ROW:
00 800 4488 8844
Toll ROW: +44 134 435 0296

OEM Sales

Phone: (425) 348-2762

Media Sales

Phone: (513) 874-5882

Customer Service and Support

Toll Free NA: (800) 755-5505
Toll in NA: (425) 356-1799

Copyright © 2010 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611834-01E 03/10

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

